

# PRODUCT INFORMATION

A PRODUCT OF AMERICAN CHEMICAL TECHNOLOGIES, INC.



## DuraLife 750M

### *High Performance Calcium Sulfonated Complex Grease with Moly*

#### DESCRIPTION:

**DuraLife 750M** is a modified, overbased, sulfonate thickened grease and represents the latest technology for multipurpose grease. It is truly the “ideal” grease for multipurpose performance within changing manufacturing environments. **DuraLife 750M** is unequalled in the areas of high temperature performance, resistance to water, mechanical stability and corrosion resistance.

#### PERFORMANCE:

**Automotive:** High dropping point and exceptional oxidation resistance make sulfonate complexes an obvious choice for long-lasing lubrication of wheel bearings, constant velocity joints, universal joints, fifth wheels, king pins and all chassis points.

**Metalworking:** Metalworking calls for lubricants with all the properties of sulfonate complexes. They are the right choice for machine tools, mechanical presses, milling heads and allied equipment, reduction gears, exposed gears, cams, toggle joints, links and other components.

**Mining:** Outstanding rust protection, combined with extreme pressure and anti-wear performance, make sulfonate complexes appropriate for use in mining applications such as rock crushers, conveyors and drilling machinery.

**Pulp and paper:** Water resistance plus corrosion inhibition make these sulfonate complex greases ideal for use in the corrosive environments often found in pulp and paper mills. Sulfonate complexes far exceed ASTM D1743 rust test requirements in both deionized and synthetic seawater. Specific applications include calendar bearings, high-speed spindles, and most other devices operating under load in moist, humid conditions.

**Steel:** In steel manufacturing, sulfonate complex greases have already begun replacing other premium greases. According to customers, overall grease consumption is lowered due to declined relubrication frequency owing to the excellent high-temperature performance of these greases. Because these greases exhibit high resistance to water, they are effective in applications where flooding or cascading coolant can contact the lubricant. Applications include: hot mill work roll bearings, cold mill work roll bearings, temper mill work roll bearings, continuous casters, plating line bearings, couplings, oscillators, torch pin rolls, automatic torches, run out rolls, cross transfer rolls, shears, blowers and traveling cranes

# DuraLife 750M

---

## PROPERTIES:

	<b>Test Method</b>	<b>DL750M</b>
Appearance		Smooth
Color		Gray
Thickener Type		Calcium Sulfonate
Thickener Content		28-34%
Texture		Smooth
NLGI Grade	ASTM D4950	2
Viscosity @ 40 °C	ASTM D445	135-165 cSt
Viscosity Index	ASTM D2270	95
Dropping Point	ASTM D566	288 °C (550 °F)
Unworked		310-340 mm
Molybdenum Disulfide		5.0%
Copper Strip Corrosion Rating	ASTM D4048	1A
Rust Prevention Rating	ASTM D1743	Pass
EP Properties (Four-Ball Method)	ASTM D2596	
Weld Point		800 kgf
OK Load (Timken Method)	ASTM D2509	65 lb-f

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence, or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by American Chemical Technologies' or others is not to be inferred from any statement contained herein.