

PRODUCT INFORMATION

A PRODUCT OF AMERICAN CHEMICAL TECHNOLOGIES, INC.



DuraLife MX

High Performance Multipurpose Grease

DESCRIPTION:

DuraLife MX is high performance extreme pressure grease exhibiting outstanding film strength and resistance to corrosive saltwater environments.

SPECIFICATIONS AND APPROVALS:

National Lubricating Grease Institute rating GC-LB

PACKAGING:

Drums, Pails and Cartridges

PROPERTIES:

	Test Method	DLMX-2	DLMX-1	DLMX-0
Appearance		Smooth	Smooth	Smooth
Color		Green	Green	Green
Thickener Type		Calcium Sulfonate Complex	Calcium Sulfonate Complex	Calcium Sulfonate Complex
NLGI Grade	ASTM D4950	2.5	1	0
Base oil Viscosity @40°C	ASTM D445	178 cSt	178 cSt	178 cSt
Grease Mobility @ 0 °F	USS DM 43	13.6 g/min	-	-
Grease Mobility @ -20 °F	USS DM 43	4.0 g/min	-	-
Dropping Point	ASTM D2265	+287°C (+550°F)	+232°C (+450°F)	+221°C (+430°F)
Cone Penetration @ 25 °C	ASTM D217			
Worked		250-280 dmm	310-340 dmm	355-385 dmm
Rust Prevention	ASTM D1743	Pass	Pass	Pass
Water washout 1 hr, 38°C	ASTM D1264	3.0%	10.0%	-
EP Properties	ASTM D2596			
Weld Point		620 kgf	500 kgf	500 kgf
OK Load	ASTM D2509	65lb-f	65lb	-
Wheel bearing leakage	ASTM D1263	5.0 g max	6.0 g max	-

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence, or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by American Chemical Technologies' or others is not to be inferred from any statement contained herein.