

LOCKN LUBE®

603.795.2298 • www.locknlube.com • sales@locknlube.com

G.Gun High-Pressure, Foot-Operated Grease Gun

GREASE CANISTER

Holds 2 gallons of grease so you spend your time greasing, not refilling.

PATENTED PRESSURE RETURN VALVE

Simply lift the foot pedal to return residual pressure back to the canister.

- Saves grease.
- Eliminates dribble and mess.
- Extends grease coupler and Zerk nipple life



COMFORTABLE CARRY HANDLE
Folds away for easy refilling.

FOOT-OPERATED PEDAL
Frees your hands and arms and delivers 10,000 psi.

CANISTER LID
Keeps contaminants out of your grease.

RUBBER FOOT MOUNTS
Ensures the G.Gun remains firm while pumping grease.

PATENTED LOCKNLUBE® GREASE COUPLER

- Ensures grease is delivered into the joint and the bearings, not around the Zerk.
- Easy lock-on mechanism allows for hands-free operation.
- Easy clip-off, regardless of pressure build up in the line. Combined with the Pressure Return Valve, you enjoy a near waste-free greasing system.

INDUSTRIAL-GRADE CONSTRUCTION
Durable and dependable.

| DESCRIPTION | SPECIFICATION |
|--------------------------|--|
| Delivery Rate | 0.09 oz (2.7 ml) per stroke |
| Delivery Pressure | 10,000 psi (690 Bar) |
| Grease Canister Capacity | Holds 282 oz (8 Kg) grease |
| Delivery Hose | 6.5 ft (2 m) x 1/4" (6.35 mm), 2 wire hydraulic hose. Burst rated at 23,206 psi (1,600 Bar) |
| Grease Coupler | Lock-on heavy-duty, high-pressure. Maximum pressure rated at 10,000 psi (690 Bar) Trigger activated lock-on for max seal to Zerk nipple |
| Coupler Thread | 1/8" NPT female |
| Pump Activation | Foot operated |
| Pump Mechanism | 2-stage self-priming with pressure return valve |
| Dimensions & Weight | L: 18 1/2" x W: 10 1/4" x H: 16 1/2" (L: 470 x W: 260 x H: 420 mm) Dry weight: 352 oz (10 kg) |
| Patents | Pressure Return Valve: WO 2010/127373 |

To order call 603.795.2298 or email sales@locknlube.com