

Technical Specification Sheet

LOCKNLUBE® - GREASE GUN COUPLER

Spring Loaded Activation Trigger

- Simply depress the trigger when locking the coupler onto the Zerk or to release the coupler when done.
- Easy clip-off, regardless of pressure build up in the line. NO MORE stuck couplers.
- No need to hold while greasing. Lock-on and free up both hands to operate your grease gun.

Sliding Sleeve

Locks the coupler onto the Zerk. When you pump grease ... it stays on!



1/8" NPT Female Thread

Standard size, fits most grease guns.



Four hardened spring steel jaws

Resilient under high pressure. Fits all DIN and SAE specification Zerk grease nipples.

Leak Free, High Pressure Seal
Patented design reduces leakage.



612 Chestnut Street, Nanaimo, BC Canada V9S 2L2
Phone: 250-739-0960 Email: sales@coastlubricants.com Web: http://coastlubricants.com

Technical Specifications

Description	Specification
Max Pressure	10,000 psi (690 Bar)
Zerk Compatibility	Fits all DIN and SAE specification Zerks (grease nipples).
Coupler Thread	1/8" NPT female thread.
Dimensions	L: 3 1/2 x W: 3/5 x H: 1 3/5 In (L: 88 x W: 16.4 x H: 41 mm)
Diameter (front coupler)	3/8 in (16 mm). Fits most recessed Zerks (grease nipples).
Weight	4 oz (100 g)
Grease Gun Compatibility	Works with all grease gun types: pneumatic, manual and electric.
Seal	Durable nitrile rubber seal for longevity under high pressure.
Lock-on Mechanism	Four hardened spring steel jaws are resilient under high pressure.
Patents	WO 2011/069172