

PRODUCT INFORMATION

A PRODUCT OF AMERICAN CHEMICAL TECHNOLOGIES, INC.



TrimLube 103 LO

Vanishing Trim Die Lubricant

DESCRIPTION:

TrimLube 103 LO replaces vanishing oils that are used in trim press and stamping operations. Its unique polymer lubricant additives provide improved tool and die life without galling and sticking. It does not build up on the press or finished parts allowing finished parts to be welded over or easily cleaned for subsequent plating or painting operations. **TrimLube 103 LO** can be used on both ferrous and non-ferrous metals and will leave a light protective film for short-term corrosion protection

TrimLube 103 LO is designed to be used as received and can be applied by spray, dip or brush applications.

PROPERTIES:

	Test Method	TL103LO
Appearance		Clear, watery
Specific Gravity @ 25 °C	ASTM D1298	0.759 g/cm ³
Flash Point	ASTM D92	>60°C (>140°F)

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence, or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by American Chemical Technologies' or others is not to be inferred from any statement contained herein.