

DCbright Goby

Vehicle-Mounted Spotlighting 2.050 - 8.200 lm



Unstoppable Light for Demanding Operations

The DCbright Goby Series delivers powerful, reliable illumination where you need it most. Engineered for extreme durability, these compact yet high-output LED work lights provide up to 7,200 lumens of crisp, clear light. With rugged IP69K and IK10 protection, wide operating temperatures, and up to 360,000 hours of lumen maintenance, the Goby is built to perform in the toughest conditions. Flexible optics, multiple power options, and precise fixture adjustment ensure maximum visibility and efficiency for any application.

DCbright Goby – Small Size. Big Power. Maximum Reliability.



GO-3-18DC

2,050 - 2,300 lm



GO-6-35DC

4,100 lm



GO-9-55DC

6,300 - 7,200 lm

Goby: Common Specifications PRO=Enhanced Version

Size

120 mm x 141 mm x 79 mm
4.7 in x 5.5 in x 3 in

Weight

Standard Aluminum:
GO-3: 1.1 kg / 2.4 lb*
GO-6 & GO-9: 1.8 kg / 4.0 lb

Operating Temperature

Standard:
-40°C / -40°F < 50°C / 122°F

Cable / Remote Driver

Housing-mounted DT04-2P

Ingress / Impact Protection



IP69K, IK10

Fixture Adjustment

-60° to +30°, continuous

Lumen Maintenance

360,000 hr, LM70*



* Specifications differ per product.

Goby: Light and Power Specifications PRO=Enhanced Version

Model	Lumens (6500K CCT)	Lm/W (100%)	Power (Watts)	Voltage	Optics	CCT	Limited Warranty
GO-3-18DC-12-24V-PRO ³	2,050	120	18	12 - 24 Vdc	14°, 38°, 70°, 14x46°	5000K ²	3 year
GO-3-18DC-12-24V ¹	2,300	128	18	12 - 24 Vdc	14°, 38°, 70°, 14x46°	5000K ²	3 year
GO-6-35DC-24V ^{1 3}	4,100	120	35	24 Vdc	14°, 38°, 70°, 14x46°	5000K ²	3 year
GO-6-35DC-12-24V	4,100	120	35	12 - 24 Vdc	14°, 38°, 70°, 14x46°	5000K ²	3 year
GO-6-55DC-24V-PRO	4,600	131	35	24 Vdc	14°, 38°, 70°, 14x46°	5000K ²	3 year
GO-6-35DC-12-24V-PRO ³	4,600	131	35	12 - 24 Vdc	14°, 38°, 70°, 14x46°	5000K ²	3 year
GO-9-13AC-HT	2,600	200	13	90-305 Vac	120°	6500K ²	3 year
GO-9-55DC-24V ^{1 3}	6,300	115	55	24 Vdc	14°, 38°, 70°, 14x46°	5000K ²	3 year
GO-9-55DC-12-24V	6,300	115	55	12 - 24 Vdc	14°, 38°, 70°, 14x46°	5000K ²	3 year
GO-9-55DC-24V-PRO ³	7,200	131	55	24 Vdc	14°, 38°, 70°, 14x46°	5000K ²	3 year
GO-9-55DC-12-24V-PRO	7,200	131	55	12 - 24 Vdc	14°, 38°, 70°, 14x46°	5000K ²	3 year
GO-9-65DC-24-ULTRA ¹	8,200	126	65	24 Vdc	14°, 38°, 70°, 14x46°	5000K ²	3 year

¹ Dual color available (2200 - 6500K)

² Optional: 1800 - 6500K

³ Marine version available